

X2



X2.055 STD / GE - X2.060 STD / GE



Power Technology.

		X2.055 STD	X2.060 STD	X2.055 GE	X2.060 GE
ENGINE					
Manufacturer		Kohler			
Engine type		KDI 1903 TCR			
Max power (ISO)	hp/kW	49 / 36	57 / 42	49 / 36	57 / 42
Engine speed at max power	rpm	2600			
Max torque	Nm	180	200	180	200
Engine speed at max torque	rpm	1200			
Cylinders / Valves - Displacement	cm ³	3 / 12 - 1900			
Emissions category		Stage V			
Exhaust after-treatment system		EGR + DOC + DPF			
Air intake system		turboaftercooler			
Fuel injection system		common rail direct injection			
Cooling system		liquid			
Engine Memo Switch		●			
CAPACITIES					
Fuel tank	l	40			
TRANSMISSION					
Transmission type		mechanical			
Clutch type		mechanical			
No. of gears - FWD+REV		● 12+12 - ○ 16+16 w/creeper			
Minimum speed	m/h	● 770 - ○ 220 (w/creeper)			
Engine speed at 30 km/h	rpm	2600			
REAR PTO					
Type		mechanical dry clutch			
Speeds	rpm	● 540/540E w/ground speed			
FRONT AND REAR AXLES					
Front axle type		rigid 4WD			
Front differential lock		● Hydralock			
BRAKING SYSTEM					
Rear braking system		● mechanical wet multi-disc			
HYDRAULIC SYSTEM					
Hydraulic circuit type - Pump type		open center - twin pump			
Flow rate - rear hitch & remotes + steering	l/min	35+20			
Rear remote valves		● 2 std - ○ 2 std + 1 w/float position			
REAR 3-POINT HYDRAULIC HITCH					
Rear hitch control		mechanical with position and draft control			
Category - Hitch type		● Cat. 1 w/ fixed ball ends - ○ Cat. 2 w/ quick-hitch hooks Cat. 1/Cat. 2 & mechanical top link			
Max lifting capacity at hitch points	kg	1200			
FRONT 3-POINT HYDRAULIC HITCH					
Front hitch type		○ mechanical Cat. 1N			
Max lifting capacity at hitch points	kg	400			
FRONT PTO					
Type		○ mechanical			
Speed	rpm	○ 1000			
CAB AND DRIVING POSITION					
Cab type		○ 4-post FOPS w/opening front window			-
Air conditioning		○ manual A/C			-
Radio system		● radio ready ○ radio and sound system			-
Fleet Management				○ ready / 3-year subscription / 5-year	
DIMENSIONS AND WEIGHTS					
Wheelbase	mm	1790		1770	
Height over ROPS min - max	mm	2124 - 2199		2030 - 2105	
Height over cab min - max	mm	2205 - 2280		-	
Height over hood min - max	mm	1230 - 1305		1131 - 1206	
Length w/front weights min - max	mm	3168 - 3504		3168 - 3504	
Overall width min - max	mm	1203 - 1638		1260 - 1615	
Shipping weight ROPS/cab	kg	1600 / 1780		1580 / -	
Gross vehicle weight	kg	3050		3050	
Rear tire size (Index Radius - IR) min - max	mm	320/70R20 (475) - 360/70R24 (550)		320/70R20 (475) - 320/70R24 (525)	
Front weights	kg	○ 4x24			

KEY: ● standard ○ option - not available