

X6.4 XTRASHIFT

		X6.420		X6.430		X6.440	
		STD	LS*	STD	LS*	STD	LS*
ENGINE							
STAGE 4 / TIER 4 FINAL		BETAPOWER		BETAPOWER		BETAPOWER	
DISPLACEMENT / NO. OF CYLINDERS / NO. OF VALVES	CM ³	4500 / 4 / 16		4500 / 4 / 16		4500 / 4 / 16	
MAX. ENGINE POWER (ISO)	HP/KW	114/84		121/89		130/95.5	
MAX. ENGINE POWER WITH POWER PLUS (ISO)	HP/KW	121/89		133/98		140/103	
MAX. TORQUE WITH POWER PLUS	NM	495		545		577	
TRANSMISSION							
HYDR. POWER SHUTTLE: 36FWD+12REV (3 POWERSHIFT SPEEDS)		•		•		•	
XTRASHIFT + SPEED FOUR + CREEPER + HYDR. POWER SHUTTLE: 48FWD+16REV		○		○		○	
ECONOMY (40 KM/H AT REDUCED ENGINE SPEED)		•		•		•	
TOP FIFTY (50 KM/H)		•		•		•	
POWER TAKE-OFF							
HYDRAULICALLY OPERATED WET MULTI-DISC CLUTCH		•		•		•	
2 SPEEDS: 540/540E RPM		•		•		•	
2 SPEEDS: 540/1000 RPM		○		○		○	
4 SPEEDS: 540/540E/1000/1000E RPM		○		○		○	
FRONT 4WD AXLE							
RIGID TYPE		•		•		•	
WITH ELECTRONICALLY-CONTROLLED HYDRAULIC SUSPENSIONS		○		○		○	
HYDRAULIC POWER LIFT							
ELECTRONIC		•		•		•	
MAX. LIFT CAPACITY WITH TWIN ASSISTOR RAMS	KG	6000		6000		6000	
HYDRAULIC PUMP FLOW (HITCH + STEERING)	L/MIN	66+38		66+38		66+38	
CLOSED CENTRE SYSTEM PUMP FLOW (HITCH + STEERING) L/MIN			110+38		110+38		110+38
CAB AND DRIVING POSITION							
MECHANICAL CAB SUSPENSION		—	○	—	○	—	○
AIR-CONDITIONING		•	○	•	○	•	○
CLIMATE CONTROL		○	•	○	•	○	•
DIMENSIONS AND WEIGHTS							
WHEELBASE	MM	2540		2540		2540	
WEIGHT WITHOUT BALLAST	KG	4700		4700		4700	

Key: • standard ○ option — not available * Load Sensing

.-500+
5BNNFM4
5VSV+HFWB
5FM
0GFBUBNNFMFF



XXXBUBNNFMFF

